


Solunar FR

Dimout dimout



pebble 2580-18 300 cm




funghi 2580-25 300 cm



hay 2580-32 300 cm



fresco 2580-49 300 cm




greige 2580-56 300 cm




ice 2580-63 300 cm




stone 2580-70 300 cm




natural 2580-87 300 cm



iris 2580-94 300 cm




petal 2581-17 300 cm



aluminium 2581-24 300 cm



gull 2581-31 300 cm




cloud 2581-48 300 cm




fog 2581-55 300 cm




slate 2581-62 300 cm



steel 2581-79 300 cm



pirate 2581-86 300 cm



night 2581-93 300 cm



ocean 2582-09 300 cm



horizon 2582-16 300 cm




sky 2582-23 300 cm




surf 2582-30 300 cm



palm 2582-47 300 cm



spice 2582-54 300 cm



mandarin 2582-61 300 cm

Name name	Solunar FR	Schwerentflammbarkeit flame resistance	DIN 4102 B1
Artikelnummer article number	2580 - 2582	Lichtechtheit lightfastness	5
Anzahl Farben number of colourways	25	IMO	A471
Höhe/Breite height/width	ca. 300 cm	Einsprung shrinkage	ca. 0 - 0,5%
Rapport horizontal repeat horizontal	---	Martindale martindale	---
Rapport vertikal repeat vertical	---	Beschwerungsband weight band	nein no
Gewicht weight	ca. 920 g/lfm	Schallabsorption sound absorption	DIN ISO 11654 $\alpha_w = 0,9$ (A)
Komposition composition	56% rec. Polyester (PES) FR, 44% Polyester (PES) FR	Pflege care labeling	    

